



## Product Data Sheet

### **AMBERSEP™ GT75 Chelating Resin**

Industrial-grade Complexing Resin

#### **Description**

AMBERSEP™ GT75 Chelating Resin is alkyl thiol-functionalized, which provides very pronounced selectivity for certain metal ions such as mercury, rhodium, copper, silver, cadmium, and lead.

AMBERSEP™ GT75 is a uniform particle size resin that has been developed for the rapid removal of mercury from different solutions and gaseous streams. Although it has a lower capacity than AMBERSEP™ GT74, it can be regenerated more readily and efficiently with hydrochloric acid.

The special properties of AMBERSEP™ GT75 make it useful for problems where removal of metal ions in addition to Hg—such as Cu, Ag, Pb, and Cd—is also desired. Applications may be found in different fields of chemical technology, for example: wastewater treatment, flue gas desulfurization blowdown, recovery of solutions and metals in the plating industry, recovery of catalysts, and removal of interfering ions in hydrometallurgy.

AMBERSEP™ GT75 is insoluble in common solvents and stable over the entire pH range. Oxidizing media should be avoided.

#### **Applications**

- Wastewater treatment
- Flue gas desulfurization blowdown
- Electroplating
- Hydrometallurgy
- Chlor-alkali streams for mercury cell electrodes

#### **Typical Properties**

---

##### **Physical Properties**

|                  |                                       |
|------------------|---------------------------------------|
| Copolymer        | Styrene-divinylbenzene                |
| Matrix           | Macroporous                           |
| Type             | Chelant                               |
| Functional Group | Alkyl thiol                           |
| Physical Form    | White to tan, opaque, spherical beads |

---

##### **Chemical Properties**

|                          |                |
|--------------------------|----------------|
| Ionic Form as Shipped    | H <sup>+</sup> |
| Total Exchange Capacity  | ≥ 0.8 eq/L     |
| Water Retention Capacity | 35 – 40%       |

---

##### **Particle Size** §

|                        |             |
|------------------------|-------------|
| Particle Diameter      | 575 ± 50 µm |
| Uniformity Coefficient | ≤ 1.1       |

---

##### **Density**

|                 |         |
|-----------------|---------|
| Shipping Weight | 675 g/L |
|-----------------|---------|

---

§ For additional particle size information, please refer to the [Particle Size Distribution Cross Reference Chart](#) (Form No. 177-01775).

## Suggested Operating Conditions

|                               |   |
|-------------------------------|---|
| Maximum Operating Temperature | 60°C (140°F)  |
| Bed Depth, min.               | 1000 mm (3.1 ft)  |
| Flowrates                     |   |
| Service                       | 10 BV*/h (1.25 gpm/ft <sup>3</sup> )                            |
| Backwash                      | About 12 m/h (5 gpm/ft <sup>2</sup> ) with water at 20°C (68°F) |
| Total Rinse Requirement       | 2 – 3 BV (15 – 22.5 gal/ft <sup>3</sup> )                       |
| Regenerant                    | Concentrated HCl  |

\* 1 BV (Bed Volume) = 1 m<sup>3</sup> solution per m<sup>3</sup> resin or 7.5 gal per ft<sup>3</sup> resin

## Application Information

The selectivity sequence of AMBERSEP™ GT75 Chelating Resin is:

Hg > Ag > Cu > Pb > Cd > Ni > Co > Fe > Ca > Na

The resin has a pronounced preference for copper, lead, and cadmium ions, which are removed in considerable quantities, even from solutions containing only 1 meq/L of metal and a large excess of Na<sup>+</sup> ions.

## Product Stewardship

DuPont has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with DuPont products—from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

## Customer Notice

DuPont strongly encourages its customers to review both their manufacturing processes and their applications of DuPont products from the standpoint of human health and environmental quality to ensure that DuPont products are not used in ways for which they are not intended or tested. DuPont personnel are available to answer your questions and to provide reasonable technical support. DuPont product literature, including safety data sheets, should be consulted prior to use of DuPont products. Current safety data sheets are available from DuPont.

Please be aware of the following:

- **WARNING:** Oxidizing agents such as nitric acid attack organic ion exchange resins under certain conditions. This could lead to anything from slight resin degradation to a violent exothermic reaction (explosion). Before using strong oxidizing agents, consult sources knowledgeable in handling such materials.

**Have a question? Contact us at:**

[www.dupont.com/water/contact-us](http://www.dupont.com/water/contact-us)

All information set forth herein is for informational purposes only. This information is general information and may differ from that based on actual conditions. Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. Please note that physical properties may vary depending on certain conditions and while operating conditions stated in this document are intended to lengthen product lifespan and/or improve product performance, it will ultimately depend on actual circumstances and is in no event a guarantee of achieving any specific results. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. No freedom from infringement of any patent or trademark owned by DuPont or others is to be inferred.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, ℠ or ® are owned by affiliates of DuPont de Nemours Inc. unless otherwise noted. ©2019 DuPont.

